

INTRODUCING

REZNOR®

RA/RAD Series Models 150 & 250 Standard Unit Heaters or Ductable Furnaces

- User-Friendly**
- Efficient and Accessible**
- Quiet On-Board Air Compressor**
- Patented Fuel Metering**
- Patented Oil-Preheating System**
- Thermostat-Controlled Operation**
- Easy Installation**
- Versatile Mounting options**
- CSA Certified to UL Standards**
- Industry's Best Warranty**



Backed by 120 years experience and the industry's largest distribution network!

800-695-1901 Ext. 2

www.ReznorHeaters.com

DESIGNED RIGHT!

New Chamber Design - Efficient and accessible

User-Friendly - Easy, quick and inexpensive to maintain

Easy Swing-Out access to combustion chamber & heat exchanger

Large, easily accessible service panels

Convenient burner service shelf

Extended times between clean-outs

Flexible Installation Options

Ceiling suspended or combined with Workbench Fuel Tank & Heater Stand

Horizontal louvers standard - Optional vertical louvers

RAD Models - Ductable ready

Efficient Air-Atomizing Burner - Proven dependability since 1991

Quiet, On-Board Air Compressor - No shop air required

Positive Displacement Metering Pump - No fuel adjustments needed

Automatic Thermostat-Controlled Operation - Just set the shop temperature you want

Patented Oil-Preheating System - Optimum combustion with no nozzle after-drip

Back-flow / Ash Sensor - Signals need for unit cleaning for peak performance

Operation Hour Meter - Confirms actual run time and prompts cleaning of unit


DESIGNED SPECIFICALLY FOR BURNING USED OILS!



Model RA-150



Model RA-250



Full Swing-Out Rear Door for easy, quick, complete cleaning

BUILT RIGHT!

Quality Assurance - Materials, fabrication and final product

Heavy Gauge Combustion Chamber/Heat Exchanger - Long life performance


Baked-on, Durable Enamel Finish - Crack and peel resistant

CSA CERTIFIED FOR OPERATION AND EFFICIENCY!

BACKED RIGHT!

Nation's largest distributor network - Local after-sales support when you need it.

Whatever the application, there's a Reznor Heater perfect for you!



Fan Unit Heaters



Blower Ductable Furnaces



Recycling Center: Unit Heater, Workbench Tank and Heater Stand

TECHNICAL DATA	Model RA (Fan-Type Unit Heater)		Model RAD (Blower-Type Unit Heater)	
	150	250	150	250
Size	150,000	250,000	150,000	250,000
BTUH Input	120,000	200,000	120,000	200,000
BTUH Thermal Output	1.05	1.75	1.05	1.75
Nozzle Input (GPH)	1050	1050	1725	1725
Motor RPM	1/4	1/2	1/2	3/4
Motor HP	115V-15	115V-21	115V-18	115V-22
AMPS Full Load	2050	3300	2050	3150
CFM (free air)	--	--	1600	2850
CFM .25" ESP - RAD only	50ft (15M)	65ft (20M)	50ft (15M)	65ft (20M)
Air Throw (9-ft suspension)	18-30°	24-28°	12-9	15-11
Fan Dia/Pitch & Blower Size	8	8	8	8
Flue Size (inches)	320	370	360	430
Approximate Net Wt (lbs)	380	440	435	520
Approximate Shipping Wt (lbs)				



NOTE: The use of waste oils on-site in a waste oil heater is an approved method of recycling by the Environmental Protection Agency (EPA). By local codes, it is not approved in California and New York City. Some other areas may require permits.

OPTIONAL ACCESSORIES (Field Installed)

- Vertical Louvers - Hanger Kit - Vent cap
- Workbench Fuel Tank with or without Heater Stand